Quick Guide Product Selector

Verplas Thermal 125mm Round:













										V	DOCTING
Product Code & Desc		Free Area: mm²	8 l/s	13 l/s	21 l/s	30l/s	60 l/s	120 l/s	Max / Min Temperature: °C	Weight: g	Application
Self-Seal Thermal Round Pipe	DS: 125mm x 1m SST - 125 - 1M	12,273mm²	0.10 pa	0.20 pa	0.40 pa	0.80 pa	3.10 pa	11.60 pa	+ 60°C to - 15°C	3 4 1g	
	DS: 125mm x 2m SST - 125 - 2M	12,273mm²	0.20 pa	0.40 pa	0.90 pa	1.70 pa	6.00 pa	22.30 pa	+ 60°C to - 15°C	682g	
Self-Seal Thermal 90° Round Elbow Bend	DS: 125mm SST - 125 - 90B	12,273mm²	0.40 pa	1.00 pa	2.40 pa	4.90 pa	19.20 pa	76.80 pa	+ 60°C to - 15°C	193g	
Self-Seal Thermal 45° Round Elbow Bend	DS: 125mm SST - 125 - 45B	12,273mm²	0.10 pa	0.30 pa	0.80 pa	1.50 pa	5.20 pa	19.80 pa	+60°C to -15°C	167g	£ 6 @ 4
Self-SealThermal Equal T Piece	DS: 125mm SST - 125 - TP	12,273mm²	N/A	N/A	N/A	N/A	N/A	N/A	+ 60°C to - 15°C	270g	. 6 6 4
Self-Seal Thermal Round Condensation Trap Coming 2016	DS: 125mm SST - 125 - TRAP	ТВС	TBC	ТВС	ТВС	ТВС	ТВС	ТВС	ТВС	ТВС	ТВС
Self-Seal Thermal Round Duct to Duct Connector	DS: 125mm SST - 125 - DDCON	12,273mm²	N/A	N/A	N/A	N/A	N/A	N/A	+ 60°C to - 15°C	N/A
Self-Seal Thermal Round Duct to Fitting Connector	DS: 125mm SST - 125 - DFCON	12,273mm²	N/A	N/A	N/A	N/A	N/A	N/A	+ 60°C to - 15°C	N/A	